

# R50 Contactless Card Reader

- Visa & MasterCard NFC
- 4 ATM-style keys
- Large capacity memory
- Durable stand with wide range of adjustment angles
- Integrates smoothly to any stand-alone payment device

PAX's R50 contactless card reader is sleek and elegant, versatile and highly reliable, enabling retailers and consumers alike to conduct an increasing share of small-value payment transactions. The stylish R50 readily connects to any electronic payment device for easy contactless upgrade.

The built-in buzzer signals the card holder when the card is read, providing reassurance that the transaction has been processed. The R50 supports the leading contactless MSD and EMV program specifications from Mastercard and Visa .

The R50 has a powerful 32-bit ARM 9 CPU and 24 MB memory that enable the development and operation of multiple types of payment applications. The optional USB cable and large adjustable stand makes the R50 a flexible solution for a variety of installations.

Your Payment Partner of Choice



# R50 Contactless Card Reader

# Features & Benefits





- Supports contactless applications
  - MasterCard Contactless
  - Visa payWave
  - American Express ExpressPay
  - Discover Zip
  - Interac Flash
  - SoftCard
  - QPBOC L1/L2
- 4 ATM-style keys (optional)
- Large capacity memory
- Durable stand with wide range of adjustment angles
- Integrates smoothly to any stand-alone

# **Specifications**

# Processor

32-bit ARM9

#### Memory

24MB (8MB Flash, 16MB SDRAM)

### Display

Optional: 128 x 64 pixel LCD White backlit 4 lines of display

4 Indicators

#### **Contactless Card Reader**

MasterCard Contactless Visa payWave ISO / IEC 14443 Type A/B, Mifare compliant ISO / IEC 18092 (NFC, FeliCa) Maximum effective distance up to 4cm American Express Expresspay, Discover Zip compliant

#### **Card Slots**

4SAM Slots, ISO7816

# **Peripheral Ports**

1 x RS232 or 1 x USB

#### **Buzzer**

95dB

# **Environmental**

 $0^{\circ}\text{C}$  to  $50^{\circ}\text{C}$  (  $32^{\circ}\text{F}$  to  $122^{\circ}\text{F}$  ) operating temperature 5% to 90% relative humidity, non-condensing -20°C to 70°C (-4°F to 158°F) storage temperature

# Voltage (optional)

External power supply DC5V, 500mA

#### **Physical**

Reader: Length: 137mm Width: 88mm Height: 28mm

#### Base

Length: 115mm

Width: 80mm Height: 55mm

# Weight

260g

# Certifications

MasterCard Contactless Visa payWave American Express ExpressPay Discover Zip Interac Flash SoftCard EMV Contactless L1 QPBOC L1/L2

